

# TIRE INFORMATION GUIDE



5775 NW WAGON WAY / HILLSBORO, OR 97124-8531 / ph: 866.531.0600 / fx: 503.531.0601

Model	Beam Capacity	Brake Size	Wheel or Hub Type	Rim Size	Tire Size	Tire O.D.	Loaded Radius
Wheels accepting demountable rims preferred for axle capacities of 40,000 lbs. and over.							
T-37	40,000	20 x 8	10 stud 13 <sup>3</sup> / <sub>16</sub> B.C.	H 8.50-24 8.50-25	P 12.00-24 P 12.00-25	49.6	23.3
T-37	40,000	20 x 8	Wheel for Dual Demountable Rims	S 8.50-24 8.50-25	P 12.00-24 P 12.00-25	49.6	23.3
S-54	60,000	20 x 8	Wheel for Dual Demountable Rims	S 10.00-24 10.00-25	P 14.00-24 P 14.00-25	54.0	25.1
S-55	60,000	20 x 8	10 stud 13 <sup>3</sup> / <sub>16</sub> B.C.	H 10.00-24 10.00-25	P 14.00-24 P 14.00-25	54.0	25.1
S-65	75,000	20 x 8	12 stud 15 B.C.	H 11.25-25 13.00-25	P 16.00-25 P 18.00-25	57.2 63.8	26.3 29.2
S-65	75,000	20 x 8	Wheel for Dual Demountable Rims	S 11.00-25 13.00-25	P 16.00-25 P 18.00-25	57.2 63.8	26.3 29.2
S-65	75,000	20 x 8	12 stud and single Fabricated Wheel	H 25.00-29	29.5-29	77.4	35.1
S-65	75,000	20 x 8	12 stud and single Fabricated Wheel	H 22.00-33	27.00-33	88.7*	40.0*

\*This information varies with tire selected.

Tire and rim manufacturer's data must be verified for each application. Specifications are nominal only.

H=Hub      S=Spoke Wheel      P=Preferred Applications